

PH6000FWE Winch Pack

- 6000lbs/2721kg rolling load line pull
- 12v or 24v DC
- Lightweight at 29lbs/14kg
- Free wheel
- Supplied with 6mm diameter, 90ft/27.4m wire rope & hook assembly
- Full accessories kit included:

part numbers	
654-000030	90ft/6mm diameter wire rope and hook assembly
560-000016	3 button remote with emergency stop
195-000058	12v solenoid without wiring for overload
	or
195-000059	24v solenoid without wiring for overload
055-000078	Left hand fabric winch cover
150-000028	Large roller fairlead
	Fitting nuts and bolts (for bolting winch to vehicle)
562-000021	Winch Operating & Maintenance Handbook

> APPLICATIONS

- Plant trailers
- Hunting
- ATV
- Boat trailers
- Caravans
- Car trailers
 - (motorsport)




Rolling Load Line Speed Performance

Rolling Load Line Pull (lbs/kg)	Line Speed (fpm/mpm)	Amp
No Load	19.0/5.8	20
1000/454	16.0/4.9	65
1400/635		
1600/727		
2000/907	12.5/3.8	110
2500/1136		
3000/1360	9.3/2.81	150
3300/1497		
4000/1814	6.4/2.0	190
4200/1905		
5000/2268	3.3/1.0	220
6000/2721	Stall	250

Layers/Length of Cable/Operational Rolling Load Line Pull

Layer of Cable	Total Cable on Drum (feet/metres)	Rolling Load Line Pull (lbs/kg)
1st	7/2.1	6000/2721
2nd	15/4.6	5000/2268
3rd	24/7.3	4200/1905
4th	34/10.4	3500/1587
5th	45/13.7	3100/1406



Penny Hydraulics Limited Station Road | Clowne | Chesterfield Derbyshire | S43 4AB | UK t +44 (0) 1246 811475 | f +44 (0) 1246 810403 e sales@pennyhydraulics.com w pennyhydraulics.com



12/14 ver 1. This document and all designs, images, words, logos and products contained therein are the property of Penny Hydraulics Limited and must not be copied or amended in part or in whole unless prior, express written permission is obtained from the Company. © Penny Hydraulics Limited 2014. Designed & produced by walkersdesign.co.uk